

Plug & Play

5KW/10KWh All in One

home solar battery storage system



Product Specification

- Auto ID
- Automatically assign any host
- Smart Temperature Control
- Smart parallel technology compatible with batteries with different SOC and voltages

Efficiency with up to 90% usable energy
IP20 Protection Rating
Modular design, natural cooling, indoor
Supports up to 6 units in parallel, with a total capacity of up to 60 kWh
Intelligent temperature control guarantees battery safety and longevity
Cycle life exceeds 6000 cycles for long-lasting reliability.



Shenzhen Enershare Technology Co.,Ltd

Tel: 0086-755-28748610 E-mail: wesleyyan@enershare.cn

<https://www.enershare.cn>

5KW / 10KWh All in One

Technical Specification

Model no	ES S5k200
AC Input/Output Parameters	
Ac Input voltage	AC 230 V
Optional Voltage	170-280V AC(Personal Computer)
Optional Voltage	90-280v AC(Home Load)
Frequency Range	50Hz/60Hz (Auto Sensing)
Max AC Charge Current	60A @DC 57.6V
AC Output Voltage	230V AC ±5%
Eciency (Peak)	Upto 93.5%
Transfer Time	10ms (Personal Computer); 20ms (Home Load)
Surge Power	11000VA
Waveform	Pure Sine Wave
PV Voltage Range	120V-450V DC
Max. PV Open Circuit Voltage	500V DC
Max. Solar Charge Current	100A @ 57.6 DC
Max. PV Array power	6000W
Battery Parameters	
Battery Type	Lithium iron phosphate
Normal Voltage	51.2V
Normal Capacity	10.24kWh
Useable Capacity	10kWh
Operating Voltage	48~57.6V
Rated Charging current	50A
Max Charging Current	100A
Recycle Time	6000 (@25C, DoD 90%)
Enviornment Requirments	
Humidity	5% to 90% Relative Humidity
Battery Recycle Tlme	6000 (@25C, DoD 90%)
Operating Temprature	-10° C to 50° C
Storage Temrature	-10° C to 60° C
Warranty	5 Years